



Shell Helix City 0W-16

Fully Synthetic Passenger Car Motor Oil

Shell Helix City is designed for drivers to protect engines running efficiently in demanding driving conditions and in busy traffic with start-stop mode.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

Everyday motorway or city driving can mean severe conditions for engine oil. Shell Helix City helps to extend engine life by protecting against wear in demanding daily traffic conditions.

Specifications, Approvals & Recommendations

- ILSAC GF-6B
- API SP

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk

Typical Physical Characteristics

Properties		Method	Shell Helix City 0W-16
Viscosity Grade			0W-16
Service Category			SP-Resource Conserving
			GF-6B
			N/A
Density	kg/m ³	ASTM D4052	834
Flash Point	°C	ASTM D92	240
Pour Point	°C	ASTM D97	-50
Kinematic Viscosity	@40°C cSt	ASTM D445	37.45
Kinematic Viscosity	@100°C cSt	ASTM D445	7.060
Viscosity Index		ASTM D2270	153

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

