

Shell Gadus S5 V100CSK

Technical Data Sheet

- Long Life
- Improved Efficiency
- Lithium Complex

Advanced Multipurpose Grease

Shell Gadus S5 V100CSK is a lithium complex grease based on synthetic base oils, containing antioxidants, wear- and rust preventing additives

The product contains a special friction modifier which is suitable for high speed bearings, taper roller bearings and cylindrical bearings, type NJ, NUP plus applications with an angle ring.

DESIGNED TO MEET CHALLENGES

Main Applications









Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Gadus S5 V100CSK
NLGI Consistency				2
				Light Brown
Dropping Point		°C minimum	IP 396	220
Base Oil Viscosity	@40°C	cSt	IP 71 / ASTM D445	100
Base Oil Viscosity	@100°C	cSt	IP 71 / ASTM D445	14
Rust Preventing Properties : SKF Emcor distilled water				0/0

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

· Heath, Safety & Environment

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from https://www.epc.shell.com

Protect the Environment Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Additional Information

Advice

Advice on applications not covered here may be obtained from your Shell representative.

