

# Shell Helix Ultra Professional AJ-L 0W-30

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

Designed to meet the demanding requirements of particular high-performance engines from Jaguar-Land Rover and Ford and those requiring ACEA C2

# Proud Drivers Choose Shell Helix

# **Main Applications**

 Shell Helix Ultra Professional AJ-L for diesel engines is approved against the technically challenging in-house technical requirements of the Jaguar Land Rover engineoil specification STJLR.03.5007

# Specifications, Approvals & Recommendations

- API SN
- ACEA C2
- Jaguar Land Rover STJLR.03.5007
- Ford WSS-M2C950-A
- meets requirements IVECO 18-1811 SC1 LV 16
   To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
   https://www.shell.com.au/motorists/oils-lubricants/lubematch.html#iframe=LyMv

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

#### **Typical Physical Characteristics**

Properties			Method	Shell Helix Ultra Professional AJ-L 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	9.80
Kinematic Viscosity	@40°C	cSt	ASTM D445	52.00
Viscosity Index			ASTM D2270	179
MRV	@-40°C	cР	ASTM D4684	14 400
Density	@15°C	kg/m³	ASTM D4052	833.5
Flash Point		°C	ASTM D92	233
Pour Point		°C	ASTM D97	-54

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

# Health, Safety & Environment

### · Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on health and safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from https://epc.shell.com

# · Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Technical Helpdesk 1300 134 205