



Shell Rotella® T5 10W-30 (CJ-4) • *Low Emissions* • *Energy Saving*

Synthetic Blend Technology Heavy Duty Diesel Engine Oil

Shell Rotella® T5 Energised Protection™ oil features "Low-SAPS" additive technology for increased compatibility with the latest exhaust emissions control systems while delivering energy savings. Protective power is further enhanced through the use of synthetic base oil technology that increases additive activity to deliver fuel economy performance with no compromise in durability.



Performance, Features & Benefits

• Emissions system compatibility

Advanced low-ash formulation helps control the blocking or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.

• Fuel economy capability

The use of synthetic base oil components provides Shell Rotella® T5 with the capability to improve cold starting and reduce fuel consumption and save money, without compromising engine protection or durability.

• Improved engine cleanliness

The advanced formulation delivers good engine cleanliness and protection against piston deposits ensuring engine and component reliability at extended oil drain intervals.

• Low emission engine use

Shell Rotella® T5 meets the requirements of the major US and European engine manufacturers for low emission applications.

Specifications, Approvals & Recommendations

- API: CJ-4, SM
- ACEA: E9, E7
- Caterpillar: ECF-3, ECF-2
- Cummins: CES 20081
- DDC : 93K218
- Ford : WSS-M2C171-E
- JASO: DH-2
- Mack: EO-O Premium Plus
- MAN: M 3575
- MB Approval: 228.31
- MTU: Cat 2.1
- Volvo: VDS-4

Main Applications



For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Rotella T5 (CJ-4)
SAE Viscosity Grade				10W-30
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	78.9
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	12
Dynamic Viscosity	@-25°C	mPa s	ASTM D5293	6000
Viscosity Index			ASTM D2270	147
Total Base Number	mg KOH/g		ASTM D2896	10
Sulfated Ash	%		ASTM D874	1.0
Density	@15°C	kg/l	ASTM D4052	0.847

Properties		Method	Shell Rotella T5 (CJ-4)
Flash Point (COC)	°C	ASTM D92	225
Pour Point	°C	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Rotella® T5 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.